



TILE COAT ELASTOMERIC EMULSION FOR EARTHEN ROOF TILES

Tile Coat is a unique formulation intended to protect roof tiles from the continuous heavy rain, scorching sun, humidity, fungal and algae infestation, flaking etc. It is an Elastomeric Emulsion paint based on 100% acrylic emulsion, ultra-violet resistant pigments, imported preservatives, and special additives.

It is used on sloping earthen tile roofs, exterior earthen wall tiles, exterior brick walls, and interior earthen wall & ceiling tiles.

SURFACE PREPARATION

- Ensure that the surface is thoroughly clean, dry, and free from all loose dirt, chalk, grease, fungi, algae and flaking paint, through high pressure water jetting
- For areas severely affected by algae or fungus, application of anti-fungal Pre-Treatment Coat is recommended
- Do not apply during wet weather
- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application
- Do not apply any kind of putty or primer

APPLICATION

- Thinning: Dilution % (by volume), 20-40% (brush or spray)
- New Tiles: For best results apply 1st coat by dipping the tile in a bucket filled with diluted Tile Coat as per the thinning instruction. Allow the tile to dry for 4-6 hours. Fully dried tiles are to be laid on the roof. After complete laying of tiles, apply the second coat using brush or spray
- Old Pre-painted tiles and other substrates: Apply two coats of Tile Coat after proper surface preparation, with 4-6 hours between coats. Apply using brush, roller or spray

PERFORMANCE FEATURES AND BENEFITS

- Unique water repellent properties
- Resistance to ultraviolet rays
- Fungus and algae resistance
- Long-lasting rich glow
- Fast protection
- Beautiful looks

PACK SIZE AVAILABILITY: 1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr

BASE & SHADE RANGES:

Mangalore tile, Sunrise, Terracotta Red, Grape Brown, Flame Red, Iron Ore Grey, New Flame, Orchid Grape, Electric Blue, Antique brown, Sunset, Silent Night

TECHNICAL DATA

A) COVERAGE*	B) DRYING TIME	C) GLOSS LEVELS/ SHEEN LEVELS	D) FLASH POINT (IS 101/1987, PART 1, SEC 6)	E) STABILITY OF THINNED PAINT	F) SHELF-LIFE
On smooth Roof Tiles 2 coats : 60-80 sq.ft /Ltr	Surface dry time - 45 minutes	10-20 units at 60° gloss head	NA	Use within 24 hrs	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat

*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

*Conditions Apply

**true
coat**
Paints for Perfection

Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.

IV/14-B, Kaninad P.O, Puthencruz, Kochi.

93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com