



## TRUECOAT PAINTS ACRYLIC INTERIOR WALL PUTTY

Truecoat Paints Acrylic Interior Wall putty is a water-based ready-to use putty that provides a very durable foundation, and brings out the best performance from the finish paints, both in looks and in durability.

This putty is meant for filling and smoothening cracks and dents on plastered walls, wooden surfaces, interior masonry, asbestos or concrete.

### SURFACE PREPARATION

- Ensure that the surface is thoroughly clean, dry, and free from all loose dirt, chalk, grease, fungi, algae and flaking paint, through high pressure water jetting
- For areas severely affected by algae or fungus, application of anti-fungal Pre-Treatment Coat is recommended
- Do not apply during wet weather
- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application
- Do not apply any kind of putty or primer

PACK SIZE AVAILABILITY: Available in  
1kg, 2kg, 5 kg, 10 kg, 20 kg

SHADE RANGE: White

### METHOD OF APPLICATION

Apply 2-3 coats of wall putty as given below.

SUBSTRATE/UNDERCOATS	THINNER	DILUTION %	APPLICATION VISCOSITY	RECOATING PERIOD
On smooth Roof Tiles 2 coats: 60-80 sq.ft /Ltr	Water (if required)		Paste	4-6 hrs
Truecoat Acrylic Interior Wall Putty 2nd Coat putty knife	Water (if required)		Paste	4-6 hrs

### TECHNICAL DATA

A) COVERAGE*	1 coat: 10-30sq.ft/kg
B) DRYING TIME	Surface dry time –45 minutes
C) GLOSS LEVELS/SHEEN LEVELS	NA
D) FLASH POINT (IS 101/1987, PART 1, SEC 6)	Non flammable
E) STABILITY OF THINNED PUTTY	Use within 8 hours
F) SHELF-LIFE	1.5 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat

\*Conditions Apply

**true  
coat**  
Paints for Perfection

Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.

IV/14-B, Kaninad P.O, Puthencruz, Kochi.

93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com