



DIVA LUXURY INTERIOR EMULSION

"DIVA" - Luxury Interior Emulsion is an exquisite emulsion paint formulated in a balanced manner with properties like dispersion, sheen level, anti-fungal, anti-fading and minimum porosity. It also provides high washability and is easy to maintain. It maintains its fresh look for years. It gives a smooth sheen finish at an affordable price.

"DIVA" - is an interior wall finish that can be applied on all types of Sand /cement plaster surface, false ceilings, asbestos sheets, brickwork, concrete block and fibreboard.

SURFACE PREPARATION

- For fresh/ new surfaces, sand the surface with Emery Paper No.80 and wipe clean. Apply the first coat of primer and allow it to dry for 6 to 8 hours. Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight. Sand the surface with Emery Paper No.100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 to 8 hours. Sand the surface with Emery Paper No.220 and wipe clean.
- For previously painted surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

APPLICATION

Dilute the paint in 30% ratio. Apply the first finish-ing coat and allow it to dry for at least 6 to 8 hours. After the first coat dries, apply the second coat and allow it to dry overnight. Apply 2 coats of DIVA Emulsion for re- painting provided the colour is same. For fresh painting it is advisable to give 3 coats for a rich look.

PERFORMANCE FEATURES AND BENEFITS

- Soft sheen, non- stick paint film
- Very high washability and scrub resistance
- Longer life and easy maintenance.
- It is free from any heavy metal like lead, mercury and chromium
- It has excellent flow giving a near brush mark free finish.

PACK SIZE AVAILABILITY: -1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr
BASE & SHADE RANGES: -Brilliant White & Light Base

TECHNICAL DATA

COVERAGE*	On smooth primed masonry surface by brushing	2 coats : 120-130 sq.ft / Ltr
DRYING TIME	Surface Dry: 20-30 minutes depending on weather conditions	Hard Dry: 6-8 hours
GLOSS LEVEL	5 -15 at 60° Gloss head	
FLASH POINT	100% water-based paint, hence NR	
POT LIFE OF THINNED MATERIAL	Overnight	
SHELF-LIFE	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat.	

*Conditions Apply

**true
coat**
Paints for Perfection

Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.
IV/14-B, Kaninad P.O, Puthencruz, Kochi.
93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com