



IMPREZZA WEATHER PROOF EXTERIOR EMULSION

IMPREZZA Weather Proof Exterior Emulsion is a waterbased 100% acrylic exterior wall Finish, formulated with special grade emulsions, light fast pigments, unique additives which imparts anti-fungal, anti-foaming, anti-flaking and anti-fading properties. In addition, it has the unique "one-way barrier" which enables the paint film to breathe out moisture.

IMPREZZA can be applied on all types of Sand /cement plaster surface, false ceilings, asbestos sheets, brickwork, concrete block and fibreboard.

SURFACE PREPARATION

- For fresh/new surfaces, strip all the loose particles from the surface with wire brushing and by scraping, followed by a wipe down. Wash the surface down with water and allow it to dry. For better results, apply 1 or 2 coats of Bio-Wash solution by brush (optional) and allow it to dry overnight. Wash it again the next day with potable water thoroughly. Allow the surface to dry fully. Apply one coat of primer and allow it to dry for 6 to 8 hours.
- For previously painted surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

APPLICATION

Dilute the paint in 30% ratio. Apply the first finish-ing coat and allow it to dry for at least 6 to 8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

PERFORMANCE FEATURES AND BENEFITS

"IMPREZZA" is a high performance, long-lasting exterior paint specially formulated to withstand extreme tropical conditions of high rainfall, humidity, and heat. "IMPREZZA" provides excellent resistance against the growth of algae and fungi on the walls. "IMPREZZA" offers excellent protection against alkali and U V degradation.

PACK SIZE AVAILABILITY: -1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr
BASE & SHADE RANGES: - Brilliant White, AB-2 and AB-17 bases

TECHNICAL DATA

COVERAGE*	On smooth primed masonry surface by brushing	2 coats : 60-70 sq.ft / Ltr
DRYING TIME	Surface Dry: 25-35 minutes depending on weather conditions	
GLOSS LEVEL	4 -8 at 60° Gloss head	
FLASH POINT	100% water-based paint, hence NR	
POT LIFE OF THINNED MATERIAL	Overnight	
SHELF-LIFE	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat.	

*Conditions Apply



Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.
IV/14-B, Kaninad P.O, Puthencruz, Kochi.
93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com