

MAPLE ACRYLIC WASHABLE DISTEMPER

"Maple" Acrylic Washable Distemper is a water-based, interior wall paint, which gives walls a delightful, attractive, matt finish that lasts.

It can be applied on all types of plasters, false ceiling, asbestos sheets, concrete. It is designed for interiors.

SURFACE PREPARATION

- For fresh/ new surfaces, sand the surface with Emery Paper No.80 and wipe clean. Apply the first
 coat of primer and allow it to dry for 6 to 8 hours. Smoothen the surface by applying thin coats
 of putty to fill in all the dents. Allow the putty to dry overnight. Sand the surface with Emery
 Paper No.100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 to 8 hours.
 Sand the surface with Emery Paper No.220 and wipe clean.
- For previously painted surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

APPLICATION

- Dilute the paint in 30% ratio. Apply the first finish-ing coat and allow it to dry for at least 6 to 8 hours.
- After the first coat dries, apply the second coat and allow it to dry overnight.

PERFORMANCE FEATURES AND BENEFITS

It gives unmatched durability and a smooth finish that has no equal in the distemper category. It is a time-tested formulation with acrylic copolymer binder that gives it this unparalleled performance. Its special formulation ensures shade retention for a long time and its fast-drying property facilitates quicker completion of painting jobs.

PACK SIZE AVAILABILITY: -1kg, 5 kg, 10 kg, 20 kg. BASE & SHADE RANGES: - White, Light base



| TECHNICAL DATA | | |
|------------------------------|----------------------------------------------------------------------------------------------------------------|----------|
| COVERAGE* | On smooth primed masonry surface by brushing 2 coats: 80-90 sq.ft / Ltr. | |
| DRYING TIME | Surface Dry: 25-35 minutes depending on weather conditions Hard Dry: 4-6 hours | |
| GLOSS LEVEL | Matt | |
| FLASH POINT | 100% water-based paint, hence NR | |
| POT LIFE OF THINNED MATERIAL | Overnight | |
| SHELF-LIFE | 3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessiv | re heat. |
| METHOD OF APPLICATION | Brush, roller or spray | |
| | | |

Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.

IV/14-B, Kaninad P.O, Puthencruz, Kochi.

93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com