

## PERFORMANCE FEATURES AND BENEFITS

MAX Exterior Emulsion offers excellent resistance to chalking, cracking and weathering. It gives cleaner shades and Matt finish, which do not fade and last longer. It also offers good anti-algal performance in dry to moderately humid climatic conditions.

PACK SIZE AVAILABILITY: -1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr. BASE G SHADE RANGES: - Brilliant White, AC-2, AC-7, AC-9

MAX can be applied on all types of Sand /cement plaster surface, false ceilings, asbestos sheets,brickwork, concrete block and fibreboard.

## SURFACE PREPARATION

- For fresh/new surfaces, strip all the loose particles from the surface with wire brushing and by scraping, followed by a wipe down. Wash the surface down with water and allow it to dry. For better results, apply 1 or 2 coats of Bio-Wash solution by brush (optional) and allow it to dry overnight. Wash it again the next day with potable water thoroughly. Allow the surface to dry fully. Apply one coat of primer and allow it to dry for 6 to 8 hours.
- For previously painted surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

## APPLICATION

- Dilute the paint in 30% ratio. Apply the first finish-ing coat and allow it to dry for at least 6 to 8 hours.
- After the first coat dries, apply the second coat and allow it to dry overnight.

TECHNICAL DATA		TECHNICAL DATA
	COVERAGE*	On smooth primed masonry surface by brushing 2 coats: 50-60 sq.ft / Ltr.
	DRYING TIME	Surface Dry: 25-35 minutes depending on weather conditions Hard Dry: 4-6 hours
	GLOSS LEVEL	Matt
	FLASH POINT	100% water-based paint, hence NR
	POT LIFE OF THINNED MATERIAL	Overnight
	SHELF-LIFE	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat.
	METHOD OF APPLICATION	Brush, roller or spray



Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.

IV/14-B, Kaninad P.O, Puthencruz, Kochi.

93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com