



MAX INTERIOR EMULSION

MAX Interior Emulsion has a smooth and stylish matt finish, making it an ideal choice for the price conscious customer. It has twice the durability of distemper and is suitable for a wide variety of surfaces. Made up of special colour fast pigments with excellent anti-fading properties, it can be tinted and made available in thousands of shades.

For application, dilute the paint in 30% ratio. Apply the first finish-ing coat and allow it to dry for at least 6 to 8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

SURFACE PREPARATION

- For fresh/ new surfaces, sand the surface with Emery Paper No.80 and wipe clean. Apply the first coat of primer and allow it to dry for 6 to 8 hours. Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight. Sand the surface with Emery Paper No.100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 to 8 hours. Sand the surface with Emery Paper No.220 and wipe clean.
- For previously painted surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

AREAS OF APPLICATION

MAX can be applied on all types of Sand /cement plaster surface, false ceilings, asbestos sheets,brick-work, concrete block and fibreboard.

PERFORMANCE FEATURES AND BENEFITS

MAX Interior Emulsion is an acrylic emulsion paint that offers excellent smoothness to touch and an elegant, rich finish. It is also very durable and lasts about 1 to 2 years more than Distemper. "Pretty Max Emulsion" is a value for money emulsion, which provides the finish and durability of emulsions at a price similar to distemper.

PACK SIZE AVAILABILITY: -1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr.
BASE & SHADE RANGES: - Brilliant White, TE-1, TE-6

TECHNICAL DATA

COVERAGE*	On smooth primed masonry surface by brushing	2 coats : 80-90 sq.ft / Ltr.
DRYING TIME	Surface Dry: 25-35 minutes depending on weather conditions	Hard Dry: 4-6 hours
GLOSS LEVEL	Matt	
FLASH POINT	100% water-based paint, hence NR	
POT LIFE OF THINNED MATERIAL	Overnight	
SHELF-LIFE	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat.	
METHOD OF APPLICATION	Brush, roller or spray	

*Conditions Apply



Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.
IV/14-B, Kaninad P.O, Puthencruz, Kochi.
93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com