

## PERFORMANCE FEATURES AND BENEFITS

SUPERIA-Premium foundation Coat Emulsion offers excellent resistance to chalking, cracking and weathering. It gives cleaner shades and Matt finish, which do not fade and last longer. It also offers good anti-algal performance in dry to moderately humid climatic conditions. Primer coat is not required before applying this product.

PACK SIZE AVAILABILITY: -1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr. BASE & SHADE RANGES: - Jet Black, Gun Grey

## SURFACE PREPARATION

- For fresh/new surfaces, strip all the loose particles from the surface with wire brushing and by scraping, followed by a wipe down. Wash the surface down with water and allow it to dry.
- For previously painted surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

## APPLICATION

- Dilute the paint in 30% ratio. Apply the first finish-ing coat and allow it to dry for at least 6 to 8 hours.
- After the first coat dries, apply the second coat and allow it to dry overnight. After the first coat dries, apply the second coat and allow it to dry overnight.

TECHNICAL DATA	
COVERAGE*	On smooth primed masonry surface by brushing 2 coats: 50-60 sq.ft / Ltr.
DRYING TIME	Surface Dry: 25-35 minutes depending on weather conditions Hard Dry: 4-6 hours
GLOSS LEVEL	Matt
FLASH POINT	100% water-based paint, hence NR
POT LIFE OF THINNED MATERIAL	Overnight
SHELF-LIFE	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat.
METHOD OF APPLICATION	Brush, roller or spray



Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.

IV/14-B, Kaninad P.O, Puthencruz, Kochi.

93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com