

PERFORMANCE FEATURES AND BENEFITS

- Excellent Brightness & Whiteness
- Matt finish
- Hides ceiling imperfections
- Highlights vibrant colours of walls

PACK SIZE AVAILABILITY: -1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr. BASE & SHADE RANGES: - Brilliant White

sheets,fibreboard etc.

- Sand the surface with Emery paper 180 and wipe clean. Apply a coat of Truecoat Primer, allow drying for 6-8 hours. Smoothen the surface by filling dents with thin coats of Truecoat Acrylic Wall Putty.
- After drying for 6-8 hours, sand the surface with Emery paper 180. Wipe off loose particles. Apply another coat of primer. Allow drying for 4-6 hrs. Sand the surface with Emery paper 380 and wipe clean.

- Dilute 1 litre of Ceiling White with 200-350 ml water.
- It can be applied by brush or roller or conventional / airless spray. Normally 2 coats of paint are sufficient for complete opacity and desired finish.

I ECHNICAL DATA	
COVERAGE*	On smooth primed masonry surface by brushing 2 coats: 65-75 sq.ft / Ltr.
DRYING TIME	Surface Dry: 25-35 minutes depending on weather conditions Hard Dry: 4-6 hours
GLOSS LEVEL	4-6 at 60° Gloss head
FLASH POINT	100% water-based paint, hence NR
POT LIFE OF THINNED MATERIAL	0vernight
METHOD OF APPLICATION	Brush, roller or spray
SHELF-LIFE	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat.

