



TRIO 3 IN 1 IN-EX EMULSION PREMIUM INTERIOR EMULSION

Truecoat Paints proudly introduces a brand new innovation in painting technology - "Trio 3 in 1 IN-EX Emulsion". TRIO is a versatile water based emulsion that can be applied over all exterior, interior & ceiling surfaces. The emulsion provides a rich glow, brighter and smooth finish to the applied area due to its bright pigments, additives, extenders and super-acrylic finish. TRIO can be used as an EXTERIOR EMULSION, INTERIOR EMULSION and BRIGHT CEILING PAINT, on all types of Sand/cement plaster surfaces, false ceilings, asbestos sheets, brickwork, concrete block and fibreboard, whether it is exterior, interior or ceiling surfaces.

SURFACE PREPARATION

- Ensure that the surface is clean and free from dampness, dirt and other contamination. For areas severally affected by algae and fungi, ensure that the surface is completely cleaned before initiating the painting process.
- Freshly plastered surfaces must be allowed to cure completely. The coating process can be started after a minimum period of 30 days.

APPLICATION

- Apply a coat of Exterior Alkali Block cement primer as an undercoat.
- Apply suitable putty for finishing. 2nd coat of Exterior Alkali Block cement primer can be given on the putty finished substrate.
- Apply 2 coats of TRIO 3 in 1 IN-EX Emulsion with an interval of 5-6 hours between subsequent coats. Do not apply when the humidity is very high.

PERFORMANCE FEATURES AND BENEFITS

It provides long term resistance to chalking, cracking, weathering, fungus and mildew in moderately humid climatic conditions. An easy to maintain paint finish, TRIO 3 in 1 IN-EX Emulsion also has enhanced anti-algal properties.

PACK SIZE AVAILABILITY: - 1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr.
BASE & SHADE RANGES: - Brilliant White, TEI- 2 base.

TECHNICAL DATA

COVERAGE*	On smooth primed masonry surface by brushing	2 coats : 60-70 sq.ft / Ltr.
DRYING TIME	Surface Dry: 25-35 minutes depending on weather conditions	Hard Dry: 4-6 hours
GLOSS LEVEL	Rich Matt	
FLASH POINT	100% water-based paint, hence NR	
POT LIFE OF THINNED MATERIAL	Overnight	
SHELF-LIFE	3 years from date of manufacture in original tightly closed Containers, away from direct sunlight and excessive heat.	
METHOD OF APPLICATION	Brush, roller or spray	

*Conditions Apply



Factory & Corporate Office: TRUE COAT PAINTS PVT. LTD.
IV/14-B, Kaninad P.O, Puthencruz, Kochi.
93884 73093, 79028 65555 | sales@truecoatpaints.com | www.truecoatpaints.com